

OEM-IMU-EG320N

Commercial MEMS
IMU Combines With
SPAN Technology by
Hexagon | NovAtel to Deliver
3D Position, Velocity and
Attitude

SPAN: Tightly-Coupled GNSS+INS Technology

Synchronized Position and Attitude Navigation (SPAN) technology brings together two different but complementary technologies: Global Navigation Satellite System (GNSS) positioning and Inertial Navigation Systems (INS). The absolute accuracy of GNSS positioning and the stability of Inertial Measurement Unit (IMU) measurements combine to provide an exceptional 3D navigation and attitude solution that is stable and continuously available, even through periods when satellite signals are blocked.

Low Noise Commercial MEMS

The EG320N is a Micro Electromechanical System (MEMS) IMU from Epson. It features low noise gyros and accelerometers in a small, lightweight enclosure. The EG320N enables precision measurements for applications that require low cost, high performance and rugged durability in a very small form factor. When integrated with SPAN technology by NovAtel, this IMU is ideal for size constrained applications that require accurate 3D position, velocity and attitude (roll, pitch and azimuth) data.

Require Higher Accuracy?

NovAtel receivers provide your choice of accuracy and performance, from decimeter to RTK-level positioning. For more demanding applications, Inertial Explorer® post-processing software from our Waypoint® Products Group offers the highest level of accuracy.



Benefits

- Economical
- Ideal for size constrained applications
- Easy integration with NovAtel's SPAN capable GNSS+INS receivers
- Commercially exportable
- Low 3.3 VDC power input

Features

- Low noise commercial grade gyros and accelerometers
- Small size and lightweight
- IMU data rates: 125Hz or 200Hz
- Direct SPI interface to OEM7 receivers
- SPAN GNSS+INS capability with configurable application profiles
- Non-ITAR IMU

SPAN System Performance¹

Horizontal Position Accuracy (RMS)

Single Point L1	1.5 m
Single Point L1/L2	1.2 m
SBAS ²	60 cm
DGPS	40 cm
TerraStar-L ^{3,4}	40 cm
TerraStar-C PRO ^{3,4}	2.5 cm
TerraStar-X ^{3,4}	2 cm
RTK	1 cm + 1 ppm

Data Rates

IMU Raw Data Rate	125Hz or 200Hz
INS Solution	Up to 200 Hz

Time Accuracy⁵ 20 ns RMS

Max Velocity⁶ 515 m/s

IMU Performance⁷

Gyroscope Performance

Technology	MEMS
Input rate (max)	±150 deg/sec
Bias repeatability	0.5 deg/sec
Bias instability	3.5 deg/hr
Angular random walk	0.1 deg/√hr

Accelerometer Performance

Range	±5 g
Bias repeatability	15 mg
Bias instability	0.1 mg
Velocity random walk	0.05 m/s/√hr

Physical and Electrical

Dimensions 24 × 24 × 10 mm

Weight 10 g

Power

Input voltage	+3.3 VDC
Power consumption	0.1 W

Communication Interface SPI

Environmental

Temperature

Operating	-40°C to +85°C
Storage	-40°C to +85°C

Vibration (operating)

MIL-STD-810G,
7.7 g RMS, 20 - 2000 Hz

Shock (operating) MIL-STD-810G, 40 g, 11ms

Shock (survival) 1000 g, half sine, 0.5 ms

Performance During GNSS Outages⁸

Outage Duration	Positioning Mode	Position Accuracy (M) RMS		Velocity Accuracy (M/S) RMS		Attitude Accuracy (Degrees) RMS		
		Horizontal	Vertical	Horizontal	Vertical	Roll	Pitch	Heading
0 s	RTK ⁹	0.02	0.03					
	PPP	0.06	0.15	0.020	0.010	0.020	0.020	0.090
	SP	1.00	0.60					
	Post-Processed ¹⁰	0.01	0.02	0.015	0.010	0.008	0.008	0.038
10 s	RTK ⁹	0.27	0.13					
	PPP	0.31	0.25	0.070	0.020	0.040	0.040	0.130
	SP	1.25	0.70					
	Post-Processed ¹⁰	0.01	0.02	0.015	0.010	0.008	0.008	0.038
60 s	RTK ⁹	15.02	1.63					
	PPP	15.06	1.75	0.720	0.065	0.095	0.095	0.210
	SP	16.00	2.20					
	Post-Processed ¹⁰	0.34	0.11	0.026	0.012	0.012	0.012	0.043

1. Typical values. Performance specifications subject to GNSS system characteristics, Signal-in-Space (SIS) operational degradation, ionospheric and tropospheric conditions, satellite geometry, baseline length, multipath effects and the presence of intentional or unintentional interference. 2. GPS-only. 3. Requires subscription to TerraStar data service. Subscriptions available from NovAtel. 4. TerraStar service available depends on the SPAN receiver used. See the receiver product sheet for details. 5. Time accuracy does not include biases due to RF or antenna delay. 6. Export licensing restricts operation to a maximum of 515 meters/second. 7. Supplied by IMU manufacturer. 8. Outage statistics were calculated by taking the RMS of the maximum errors over a minimum of 30 complete GNSS outages. Each outage was followed by 120 seconds of full GNSS availability before the next outage was applied. High accuracy GPS updates (fixed ambiguities) were available immediately before and after each outage. The survey data used to generate these statistics is ground vehicle data collected with frequent changes in azimuth (i.e., as normally observed in ground vehicle environments). 9. 1 ppm should be added to all values to account for additional error due to baseline length. 10. Post-processing results using Inertial Explorer software.

Contact Hexagon | NovAtel

sales@novatel.com 1-800-NOVATEL (U.S. and Canada) or 403-295-4900 | China: 0086-21-68882300 | Europe: 44-1993-848-736 | SE Asia and Australia: 61-400-883-601.
For the most recent details of this product: novatel.com

©2020 NovAtel Inc. All rights reserved. NovAtel is part of Hexagon. All trademarks or service marks used herein are property of their respective owners. NovAtel makes no representation or warranty regarding the accuracy of the information in this publication. This document gives only a general description of the product(s) or service(s) offered by NovAtel, and, except where expressly provided otherwise, shall not form part of any contract. Such information, the products and conditions of supply are subject to change without notice.